

KX6-Serie – High-Tech-Klima für Großobjekte

Übersicht KX6-Innengeräte

Nenn-Kälteleistung (kW)	2,2	2,8	3,6	4,5	5,6	7,1	9,0	11,2	14	16	22,4	28,0
Nenn-Heizleistung (kW)	2,5	3,2	4,0	5,0	6,3	8,0	10,0	12,5	16	18	25,0	31,5
Modell	22	28	36	45	56	71	90	112	140	160	224	280
Deckenkassetten												
	■	•	•	•	•	•	•	•	•	•		
	•	•	•	•	•							
	■	•	■	•	•	•	•	•	•			
				•		•						
	•	•	•									
Kanalgeräte												
	•	•	•									
	•	•	•	•	•							
	•	•	•									
	•	•	•	•	•	•	•	•	•			
											•	•
Wandgeräte												
	•	•	•	•	•	•						
Unterdeckengeräte												
		■	•	•	•	•	■	•	•			
								•	•	•		

Truhengeräte													
	■	●	■	●	■	●							
		●		●	●								
	■	●	■	●	●	●							
Türluftschieber													
	Auslegung nach Türhöhe und Türbreite												
Wärmetauscher-Anschlussmodul													
	■	■	■	■	■	■	■	■	■	●		■	●

- Verfügbare Geräte im jeweiligen Leistungsbereich
- Bauseitige Anpassung der Geräteleistung durch DIP-Schalter-Änderung eines größeren Modells

Übersicht KX6-Außengeräte

Anzahl Innengeräte (min/max)	1/6	1/8	1/8	1/15	1/19	1/22	1/36	1/40	1/36	1/40	2/44	2/49
Nenn-Kälteleistung (kW)	11,2	14	15,5	22,4	28,0	33,5	40,0	45,0	50,4	56,0	61,5	68,0
Nenn-Heizleistung (kW)	12,5	16	16,3	25,0	31,5	37,5	45,0	50,0	56,5	63,0	69,0	73,0
Modell	112	140	155	224	280	335	400	450	504	560	615	680

KX6 (2-Leiter)													
		●	●	●									
KX6 (2-Leiter)													
					●	●	●						
KX6 (2-Leiter)													
								●	●	●	●	●	●
KX6R (3-Leiter), mit Wärmerückgewinnung													

